

- IP67.100% Waterproof protection. Against lubricant and coolant, waterproof, and dust-tight. Suit for severe environment.
- Instant start, no flicking, no humming, and no UV or near-infrared radiation, with excellent color rendering white light.
- The energy consumption and electricity costs saving of LED is 3 times less than fluorescent lamps.
- Two sides cable device provides special usage such as marine and aircraft factory.
- Lampshade of Acrylic or PC on request.
- DPS series is composed of LED chips which the angle could reach to 40°.

## ■ Model/Specification


## DF6 Series

Voltage	AC100 ~240V		Power	Beam Angle	LED tube	Screw	Length with L type
Lampshade	Acrylic	PC	(Watt)	Deam Angle	LED tube	Position (C)	end cover(D)
Model No.	DF6-6XY	DF6-6XC	6W	Wide	T8/330mm	450mm	460mm
	DF6-10XY	DF6-10XC	10W	Wide	T8/580mm	700mm	710mm
	DF6-22XY	DF6-22XC	22W	Wide	T8/1200m	1360mm	1370mm

## DPS6 Series

Voltage	AC/DC 24V		Power		Screw Position	Length (D)
Lampshade	Acrylic	PC	(Watt)	Beam Angel	(C)	with L type end cover
Model No.	DPS6-10PY	DPS6-10PC	10W	Narrow(60°)	450mm	460mm
	DPS6-20PY	DPS6-20PC	20W	Narrow (60°)	700mm	710mm
	DPS6-30PY	DPS6-30PC	30W	Narrow (60°)	1040mm	1050mm
	DPS6-40PY	DPS6-40PC	40W	Narrow (60°)	1360mm	1370mm

☐ Standard Installation



Standard /L type cover: Cover with screw holes, directly to fit on the machines.

